


Vestwoods.

POWER BATTERY SYSTEM SOLUTION

VC-CUBE SERIES



Long Lifespan 4000 cycle



Supports series and parallel use



Safe and reliable
The safest LFP battery



Cell Balancing Extend lifetime of battery. Current >300mA



Bluetooth built-in
Easy to access battery status



High compatibility, support to connect with lead-acid battery

SPECIFICATION

Model	VC1206	VC1208	VC1250
Cell Type	LFP	LFP	LFP
Nominal Energy	76.8Wh	102.4Wh	640Wh
Nominal Capacity	6Ah	8Ah	50Ah
Dimensions(W*H*D)	151*94*65mm	151*94*65mm	223*178*150mm
Weight	0.75kg	0.95kg	5.6kg
Discharge Current/Max. Continuous	6A	8A	50A
IP	IP65		
Nominal Voltage	12.8V		
Operating Voltage Range	10.8V~14.6V		
Peak Discharge Current	30A@3S		
Certification	UN38.3,MSDS		

Model	VC12100	VC12200
Cell Type	LFP	LFP
Nominal Energy	1280Wh	2560Wh
Nominal Capacity	100Ah	200Ah
Dimensions(W*H*D)	307*213*169mm	520*220*270mm
Weight	11.5kg	23kg
Discharge Current/Max. Continuous	100A	100A
IP	IP65	
Terminal	M8	
Casing Material	ABS	
Operating Temperature Range	Charge : 0-55 C Discharge:-20-60 C	
Humidity Range	<95% RH	
Storage Temperature	15~35 C	
Nominal Voltage	12.8V	
Operating Voltage Range	10.8V~14.6V	
Peak Discharge Current	300A@3S	
Certification	UN38.3,MSDS,CE-EMC	

Disclaimer:

This document may contain forecast information, including but not limited to future finances, operations, product series, new technologies, etc. Due to practice the uncertainty in the actual results may differ from the predicted information. Therefore, the information in this document is for reference only and does not constitute any offer or promise. Vestwoods may modify the above information without notice.

